



Horizontal

SERIES OD e OF 80-100

ErP Energy Class

C



Horizontal water heaters are the basic product range for the most varied market requirements. Suitable for locating the heater out of sight.



- Steel tank, glass-lined "Blue Glass 4753" using flow-coating method 850°C, WRAS (BS6920-1) certified
- Ø 88 mm tank inspection flange
- Corrosion-proof magnesium anode
- Screw-in heating element in copper fitted on a flange
- Regulation and safety rod thermostat
- External casing made of sheet metal coated with epoxy powder paint
- **IPX4 protective cover on electrical parts**
- Rigid polyurethane (PU) insulation layer
- LED heating lamp shows that the heating cycle is in progress
- Stored water temperature indicator

**WARRANTY:**

- **2 YEARS ON THE TANK AND COMPONENTS**

WARRANTY:

- **5 YEARS ON THE TANKS**
- **2 YEARS ON THE OTHER COMPONENTS**

TECHNICAL DATA	U.M.	OD 80	OF 80	OF 100
Capacity	l	80	80	100
Code	RIGHT LEFT	171900 171901	171903 171904	171905 171906
Warranty	/	2	2+3	2+3
Power	kW	1,2	1,2	1,2
Voltage	V~	230	230	230
Heating time (ΔT50 °C)	min.	245	245	306
ErP Energy Class	ErP	C	C	C
ErP Test profile	ErP	M	M	L
Max. operating temperature	°C	75	75	75
Max. operating pressure	MPa	0,8	0,8	0,8
Net weight	kg	20,5	20,5	25,5
Hydraulic connections (KW-WW)	G	½"	½"	½"
Dimensional values: A/B	mm	757/258	757/258	908/409
Dimensional values: C/D	mm RH mm LH	293/344 344/293	293/344 344/293	369/419 419/369

Notes: RH = Right version , LH = Left version

